

# Safety data sheet

Page: 1/17

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## **N75-V21 Clear Hardener VOC 1L**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: hardener

Recommended use: Sprayable

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF Coatings GmbH  
Postfach 6123  
48136 Muenster  
Deutschland

Contact address:

BASF plc  
PO Box 4, Earl Road, Cheadle Hulme,  
Cheadle, Cheshire  
SK8 6QG, UNITED KINGDOM

---

Telephone: +44 161 485-6222

E-mail address: [product-safety-north@basf.com](mailto:product-safety-north@basf.com)

### 1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

---

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

#### According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (Inhalation - vapour)	H332 Harmful if inhaled.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
Flam. Liq. 3	H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

## 2.2. Label elements

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Precautionary Statements (Prevention):

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing and eye protection or face protection.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
------	---

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
-------------	--

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

Labeling of special preparations (GHS):

EUH204: Contains isocyanates. May produce an allergic reaction.

### 2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

---

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

#### Chemical nature

polyisocyanate, organic solvent

#### Hazardous ingredients (GHS)

according to Regulation (EC) No. 1272/2008

n-butyl acetate

Content (W/W):  $\geq 10\%$  -  $< 12.5\%$

CAS Number: 123-86-4

EC-Number: 204-658-1

REACH registration number: 01-2119485493-29

INDEX-Number: 607-025-00-1

Flam. Liq. 3

STOT SE 3 (drowsiness and dizziness)

H226, H336

EUH066

hexamethylene-di-isocyanate

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

Content (W/W): $\geq 0.2\%$ - $< 0.3\%$	Acute Tox. 4 (oral)
CAS Number: 822-06-0	Acute Tox. 1 (Inhalation - mist)
EC-Number: 212-485-8	Skin Corr./Irrit. 2
REACH registration number: 01-2119457571-37	Eye Dam./Irrit. 2
INDEX-Number: 615-011-00-1	Resp. Sens. 1
	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H319, H315, H330, H302, H334, H317, H335

Specific concentration limit:

Skin Sens. 1:  $\geq 0.5\%$

Resp. Sens. 1:  $\geq 0.5\%$

HDI-oligomer (trimer)

Content (W/W): $\geq 75\%$ - $\leq 100\%$	Acute Tox. 4 (Inhalation - dust)
CAS Number: 28182-81-2	Acute Tox. 4 (Inhalation - vapour)
EC-Number: 500-060-2	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H332, H317, H335
	EUH204

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**If inhaled:**

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

**On skin contact:**

Flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary. Immediate medical attention required.

**On contact with eyes:**

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

---

## **SECTION 5: Fire-Fighting Measures**

### **5.1. Extinguishing media**

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### **5.2. Special hazards arising from the substance or mixture**

Endangering substances: nitrogen oxides

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

### **5.3. Advice for fire-fighters**

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

## **SECTION 6: Accidental Release Measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective clothing. Avoid breathing vapours. Ensure adequate ventilation. Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Keep away from sources of ignition.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth. Place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): ethanol or isopropyl alcohol (50 parts); water (45 parts); concentrated ammonia solution (5 parts). A non-flammable alternative is: sodium carbonate (5 parts); water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in non-sealed container. Once this stage is reached, close container and dispose according to the waste regulations (see section 13). Ensure adequate ventilation.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Care should be taken when reopening partly used containers (pressurization!). Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep away from strongly acid and strongly alkaline materials, from oxidizing agents, amines, alcohols and water.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Precautions should be taken to minimise exposure to atmospheric humidity or water: carbon dioxide will be formed which in closed containers can result in pressurisation. Always keep in containers of same material as the original one. Observe label precautions.

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

---

Storage stability:

Storage temperature: 5.00 - 35.00 °C

### 7.3. Specific end use(s)

Please refer to the technical leaflet for further information.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

#### Components with occupational exposure limits

123-86-4: n-butyl acetate

STEL value 966 mg/m<sup>3</sup> ; 200 ppm (WEL/EH 40 (UK))

TWA value 724 mg/m<sup>3</sup> ; 150 ppm (WEL/EH 40 (UK))

STEL value 723 mg/m<sup>3</sup> ; 150 ppm (OEL (EU))

indicative

TWA value 241 mg/m<sup>3</sup> ; 50 ppm (OEL (EU))

indicative

822-06-0: hexamethylene-di-isocyanate

STEL value 0.07 mg/m<sup>3</sup> (WEL/EH 40 (UK))

Measured as: NCO

TWA value 0.02 mg/m<sup>3</sup> (WEL/EH 40 (UK))

Measured as: NCO

28182-81-2: HDI-oligomer (trimer)

TWA value 0.02 mg/m<sup>3</sup> (WEL/EH 40 (UK))

Measured as: NCO

STEL value 0.07 mg/m<sup>3</sup> (WEL/EH 40 (UK))

Measured as: NCO

#### Biological limit values (BLV)

No data available.

#### Components with PNEC

123-86-4: n-butyl acetate

freshwater: 0.18 mg/l

marine water: 0.018 mg/l

intermittent release: 0.36 mg/l

STP: 35.6 mg/l

sediment (freshwater): 0.981 mg/kg

sediment (marine water): 0.0981 mg/kg

soil: 0.0903 mg/kg

822-06-0: hexamethylene-di-isocyanate

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

freshwater: 0.0774 mg/l  
marine water: 0.00774 mg/l  
intermittent release: 0.774 mg/l  
sediment (freshwater): 0.01334 mg/kg  
sediment (marine water): 0.001334 mg/kg  
soil: 0.0026 mg/kg  
STP: 8.42 mg/l

28182-81-2: HDI-oligomer (trimer)

freshwater: 0.127 mg/l  
marine water: 0.0127 mg/l  
intermittent release: 1.27 mg/l  
sediment (freshwater): 266700 mg/kg  
marine water: 26670 mg/kg  
soil: 53182 mg/kg  
STP: 38.28 mg/l

#### Components with DNEL

123-86-4: n-butyl acetate

worker: Short-term exposure - local effects, Inhalation: 600 mg/m<sup>3</sup>  
worker: Long-term exposure - local effects, Inhalation: 300 mg/m<sup>3</sup>  
consumer: Short-term exposure - local effects, Inhalation: 300 mg/m<sup>3</sup>  
consumer: Long-term exposure - local effects, Inhalation: 35.7 mg/m<sup>3</sup>  
worker: Long-term exposure- systemic effects, dermal: 11 mg/kg  
worker: Short-term exposure - systemic effects, dermal: 11 mg/kg  
consumer: Long-term exposure- systemic effects, dermal: 6 mg/kg  
consumer: Short-term exposure - systemic effects, dermal: 6 mg/kg  
consumer: Long-term exposure- systemic effects, oral: 2 mg/kg  
consumer: Short-term exposure - systemic effects, oral: 2 mg/kg

822-06-0: hexamethylene-di-isocyanate

worker: Long-term exposure - local effects, Inhalation: 0.035 mg/m<sup>3</sup>  
worker: Short-term exposure - local effects, Inhalation: 0.07 mg/m<sup>3</sup>

28182-81-2: HDI-oligomer (trimer)

worker: Short-term exposure - local effects, Inhalation: 1 mg/m<sup>3</sup>  
worker: Long-term exposure - local effects, Inhalation: 0.5 mg/m<sup>3</sup>

## **8.2. Exposure controls**

#### Appropriate engineering controls

This can be achieved by the use of local exhaust ventilation and good general extraction. Respiratory protective equipment should be worn by spray booth operatives. Ensure adequate ventilation.

#### Personal protective equipment

Respiratory protection:



BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

half-mask with A2P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. In situations where dust may occur use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

#### Hand protection:

Further information on penetration time is available from the manufacturer of the glove.

Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Wear protective gloves. Any chemical protection glove certified according to EN 374 is suitable: e.g. butyl rubber gloves - material thickness: 0,5 mm

#### Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

#### Body protection:

chemical-resistant disposable coveralls, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

#### General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible.

Under cool dry conditions, it is possible for the isocyanate to remain unreacted in the paint film for up to 30 hours after application. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

#### Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

---

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Form:	liquid
Colour:	colourless
Odour:	specific
pH value:	not applicable
Melting point:	not determined
onset of boiling:	124.00 °C

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

Flash point:	47 °C	
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m <sup>3</sup>	
Ignition temperature:	> 200.00 °C	
Vapour pressure:	10.00 hPa (20 °C)	(calculated)
	(50 °C)	
Density:	not determined 1.119 g/cm <sup>3</sup> (20 °C)	
Viscosity, kinematic:	(40 °C) not determined 195.5 mm <sup>2</sup> /s (20 °C)	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

## 9.2. Other information

Burning rate:	The material doesn't meet the criteria specified in paragraph 33.2.1.4.4 of UN manual of tests and criteria.	(UN Test N.1 (ready combustible solids))
Self heating ability:	It is not a substance capable of spontaneous heating.	
Miscibility with water:	immiscible	
Flow time:	> 30 s	(DIN EN ISO 2431; 6 mm)

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

### 10.4. Conditions to avoid

Avoid direct contact with water. Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

### 10.5. Incompatible materials

Substances to avoid:

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

Keep away from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts with water resulting in evolution of carbon dioxide. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.

### 10.6. Hazardous decomposition products

When exposed to high temperatures hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## SECTION 11: Toxicological Information

### 11.1. Information on toxicological effects

#### Acute toxicity

Assessment of acute toxicity:

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The mixture has been assessed following regulation (EC) No 1272/2008. See sections 2 and 3 for details.

Of moderate toxicity after short-term inhalation.

#### Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Based on available Data, the classification criteria are not met.

#### Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

#### Germ cell mutagenicity

Assessment of mutagenicity:

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

Based on available Data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity:

Based on available Data, the classification criteria are not met.

#### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available Data, the classification criteria are not met.

#### Developmental toxicity

Assessment of teratogenicity:

Based on available Data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available Data, the classification criteria are not met.

#### Aspiration hazard

No aspiration hazard expected.

#### Other relevant toxicity information

Based on the properties of the isocyanate components and considering toxicological data on similar product, this product may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the occupational exposure limit. Repeated inhalation may lead to a permanent respiratory disability.

---

## **SECTION 12: Ecological Information**

### **12.1. Toxicity**

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

---

## 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

No data available concerning biodegradation and elimination.

## 12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

## 12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

## 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

## 12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

---

# SECTION 13: Disposal Considerations

## 13.1. Waste treatment methods

Observe national and local legal requirements.

Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).

Waste key:

08 01 11<sup>□</sup> waste paint and varnish containing organic solvents or other hazardous substances

Contaminated packaging:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Residues in empty containers should be neutralised with decontaminant (see section 6).

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

---

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

---

## SECTION 14: Transport Information

### Land transport

ADR

UN number UN1866  
UN proper shipping name: RESIN SOLUTION  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: Tunnel code: D/E

RID

UN number UN1866  
UN proper shipping name: RESIN SOLUTION  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user:

### Inland waterway transport

ADN

UN number UN1866  
UN proper shipping name: RESIN SOLUTION  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user:

### Transport in inland waterway vessel

Not evaluated

### Sea transport

IMDG

UN number: UN 1866  
UN proper shipping name: RESIN SOLUTION  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

Marine pollutant: NO

Special precautions for user:

### **Air transport**

IATA/ICAO

UN number: UN 1866  
UN proper shipping name: RESIN SOLUTION  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: No Mark as dangerous for the environment is needed  
Special precautions for user:

#### **14.1. UN number**

See corresponding entries for "UN number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**

Regulation: Not evaluated  
Shipment approved: Not evaluated  
Pollution name: Not evaluated  
Pollution category: Not evaluated  
Ship Type: Not evaluated

---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

## SECTION 15: Regulatory Information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 10.0 %

VOC content: 98.0 g/l

VOC content: 10.0 % organic solvents

#### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3  
, 40

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):  
Listed in above regulation: Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

### 15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

## SECTION 16: Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Flam. Liq.	Flammable liquids
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Resp. Sens.	Respiratory sensitization
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
EUH066	Repeated exposure may cause skin dryness or cracking.



---

BASF Safety data sheet according to Regulation (EC) No. 1907/2006 as amended from time to time.

Date / Revised: 26.10.2020

Version: 1.0

Date previous version: not applicable

Previous version: none

Product: **N75-V21 Clear Hardener VOC 1L**

(ID no. 50659392/SDS\_GEN\_GB/EN)

Date of print 09.11.2020

EUH204

Contains isocyanates. May produce an allergic reaction.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.