

# Safety data sheet

Page: 1/17

BASF Safety data sheet according to UN GHS 4th rev.

Date / Revised: 30.10.2021

Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

## 1. Identification

### Product identifier

## N15-020 Clear 5L

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Clearcoat product

### Details of the supplier of the safety data sheet

Company:BASF France SAS  
49, avenue Georges Pompidou  
92593 Levallois-Perret Cedex, FRANCEContact address:BASF SE  
67056 Ludwigshafen  
GERMANY

Telephone: +49 621 60-0

E-mail address: global.info@basf.com

### Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

---

## 2. Hazards Identification

### Classification of the substance or mixture

According to UN GHS criteria

Skin Corr./Irrit. 2

Eye Dam./Irrit. 2A

STOT SE 3 (Vapours may cause drowsiness and dizziness.)

Aquatic Acute 2

Aquatic Chronic 3

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Flam. Liq. 3  
Skin Sens. 1A

For the classifications not written out in full in this section the full text can be found in section 16.

## Label elements

### Globally Harmonized System, UN (GHS)

Pictogram:



Signal Word:  
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash contaminated body parts thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.

Precautionary Statements (Response):

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P370 + P378	In case of fire: Use water spray for extinction.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P337 + P313	If eye irritation persists: Get medical attention.

**Precautionary Statements (Storage):**

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Precautionary Statements (Disposal):**

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

**Other hazards**According to UN GHS criteria

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

---

**3. Composition/Information on Ingredients****Substances**

Not applicable

**Mixtures**Chemical nature

acrylic resin, organic solvent

Hazardous ingredients (GHS)According to UN GHS criteria

1,2,4-Trimethylbenzene

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Content (W/W):  $\geq 5\%$  -  $< 7\%$   
CAS Number: 95-63-6  
EC-Number: 202-436-9  
INDEX-Number: 601-043-00-3

Asp. Tox. 1  
Flam. Liq. 3  
Acute Tox. 4 (Inhalation - vapour)  
Skin Corr./Irrit. 2  
Aquatic Chronic 2  
Eye Dam./Irrit. 2A  
STOT SE 3 (irr. to respiratory syst.)  
Aquatic Acute 2  
H226, H319, H315, H332, H304, H335, H401, H411

## Ethylbenzene

Content (W/W):  $\geq 1\%$  -  $< 2\%$   
CAS Number: 100-41-4  
EC-Number: 202-849-4  
INDEX-Number: 601-023-00-4

Asp. Tox. 1  
Flam. Liq. 2  
Acute Tox. 4 (Inhalation - vapour)  
Acute Tox. 5 (oral)  
STOT RE (Auditory organ) 2  
Aquatic Acute 2  
Aquatic Chronic 3  
H225, H332, H303, H304, H373, H412, H401

## 4-Methylpentan-2-one

Content (W/W):  $\geq 3\%$  -  $< 5\%$   
CAS Number: 108-10-1  
EC-Number: 203-550-1  
INDEX-Number: 606-004-00-4

Flam. Liq. 2  
Acute Tox. 4 (Inhalation - vapour)  
Eye Dam./Irrit. 2A  
STOT SE 3 (irr. to respiratory syst.)  
Acute Tox. 5 (oral)  
Asp. Tox. 2  
H225, H319, H332, H303, H305, H335  
EUH066

## Mesitylene

Content (W/W):  $\geq 1\%$  -  $< 2\%$   
CAS Number: 108-67-8  
EC-Number: 203-604-4  
INDEX-Number: 601-025-00-5

Asp. Tox. 1  
Flam. Liq. 3  
Skin Corr./Irrit. 2  
STOT SE 3 (irr. to respiratory syst.)  
Aquatic Acute 2  
Aquatic Chronic 2  
H226, H315, H304, H335, H401, H411

Specific concentration limit:STOT SE 3, irr. to respiratory syst.:  $\geq 25\%$ 

## n-Butyl acetate

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Content (W/W):  $\geq 15\%$  -  $< 20\%$  Flam. Liq. 3  
CAS Number: 123-86-4 STOT SE 3 (drowsiness and dizziness)  
EC-Number: 204-658-1 Aquatic Acute 3  
INDEX-Number: 607-025-00-1 H226, H336, H402  
EUH066

## Xylene

Content (W/W):  $\geq 5\%$  -  $< 7\%$  Asp. Tox. 1  
CAS Number: 1330-20-7 Flam. Liq. 3  
EC-Number: 215-535-7 Acute Tox. 5 (Inhalation - vapour)  
INDEX-Number: 601-022-00-9 Acute Tox. 5 (oral)  
Skin Corr./Irrit. 2  
Eye Dam./Irrit. 2B  
STOT SE 3 (irr. to respiratory syst.)  
STOT RE (Central nervous system, Liver,  
Kidney) 2  
Aquatic Acute 2  
Aquatic Chronic 3  
H226, H320, H315, H333, H303, H304, H335,  
H373, H412, H401

## Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

Content (W/W):  $\geq 0,3\%$  -  $< 0,5\%$  Acute Tox. 5 (oral)  
CAS Number: 41556-26-7 Skin Sens. 1A  
EC-Number: 255-437-1 Repr. 2 (fertility)  
Aquatic Acute 1  
Aquatic Chronic 1  
M-factor acute: 1  
H303, H317, H361, H400, H410

## Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Content (W/W):  $\geq 0,1\%$  -  $< 0,2\%$  Acute Tox. 5 (oral)  
CAS Number: 82919-37-7 Skin Sens. 1A  
EC-Number: 280-060-4 Repr. 2 (fertility)  
Aquatic Acute 1  
Aquatic Chronic 1  
M-factor acute: 1  
M-factor chronic: 1  
H303, H317, H361, H400, H410

Solvent naphtha (petroleum), light arom.

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Content (W/W): >= 10 % - < 12,5 %	Asp. Tox. 1
CAS Number: 64742-95-6	Flam. Liq. 3
EC-Number: 265-199-0	Skin Corr./Irrit. 2
INDEX-Number: 649-356-00-4	STOT SE 3 (drowsiness and dizziness)
	Aquatic Acute 2
	Aquatic Chronic 2
	H226, H315, H304, H336, H401, H411
	EUH066

Naphtha (petroleum),hydrotreated light, Kp > 140oC

Content (W/W): >= 7 % - < 10 %	Asp. Tox. 1
CAS Number: 64742-49-0	Flam. Liq. 3
EC-Number: 265-151-9	STOT SE 3 (drowsiness and dizziness)
REACH registration number: 01211947184332	Aquatic Chronic 3
	H412, H226, H304, H336
	EUH066

For the classifications not written out in full in this section the full text can be found in section 16.

## 4. First-Aid Measures

### Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

On ingestion:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

### Most important symptoms and effects, both acute and delayed

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Symptoms: Eye irritation, allergic symptoms, dazed state, skin irritation, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

### **Indication of any immediate medical attention and special treatment needed**

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

---

## **5. Fire-Fighting Measures**

### **Extinguishing media**

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

### **Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

### **Advice for fire-fighters**

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

---

## **6. Accidental Release Measures**

### **Personal precautions, protective equipment and emergency procedures**

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

### **Environmental precautions**

Do not allow to enter drains or waterways. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency. Do not discharge into the subsoil/soil.

### **Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

---

## 7. Handling and Storage

### Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

### Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: 5,00 - 35,00 °C

### Specific end use(s)

Please refer to the technical leaflet for further information.

---

## 8. Exposure Controls/Personal Protection

### Control parameters

Components with occupational exposure limits



Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

95-63-6: 1,2,4-Trimethylbenzene  
100-41-4: Ethylbenzene  
108-10-1: 4-Methylpentan-2-one  
108-67-8: Mesitylene  
123-86-4: n-Butyl acetate  
1330-20-7: Xylene

## Exposure controls

### Personal protective equipment

Respiratory protection:

Suitable respiratory protection: e.g. half-mask with A1P2 class combination filter When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. Use A1P2 breathing-protection half mask in case of contact with aerosols.

Hand protection:

Further information on penetration time is available from the manufacturer of the glove.  
Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components.  
The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).  
Follow manufacturer's advice on use, storage, maintenance and replacement of gloves.  
The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).  
Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g.  
nitrile gloves - material thickness: 0,7 mm

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166), Required when there is a risk of eye contact.

Body protection:

chemical-resistant disposable coveralls, Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

### General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

---

## 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Form:	liquid	
Colour:	colourless	
Odour:	specific	
pH value:		
	substance/mixture is non-polar/aprotic	
Melting point:	not determined	
onset of boiling:	not determined	
Flash point:	> 26 °C	(ISO 3679)
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	36 g/m <sup>3</sup>	
Ignition temperature:	> 200,00 °C	
Vapour pressure:	(20 °C) not determined	
	(50 °C) not determined	
Density:	0,948 g/cm <sup>3</sup> (20 °C)	
Viscosity, kinematic:	(40 °C) not determined 100,1 mm <sup>2</sup> /s (20 °C)	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

### Other information

Burning rate:	The material doesn't meet the criteria specified in paragraph 33.2.4.4 of UN manual of tests and criteria.	(UN Test N.1 (ready combustible solids))
Self heating ability:	It is not a substance capable of spontaneous heating.	
Miscibility with water:		
	immiscible	
Flow time:	75 s	(DIN EN ISO 2431; 4 mm)

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### **Possibility of hazardous reactions**

Vapours may form ignitable mixture with air.

### **Conditions to avoid**

Avoid direct sunlight. Avoid all sources of ignition: heat, sparks, open flame.

### **Incompatible materials**

Substances to avoid:

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

### **Hazardous decomposition products**

:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## **11. Toxicological Information**

### **Information on toxicological effects**

#### Acute toxicity

Assessment of acute toxicity:

Based on available data, the classification criteria are not met.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated and prolonged exposure to solvents at levels significantly above OELs may lead to the development of long-lasting central nervous system disorders such as chronic toxic encephalopathy, signs of toxicity include changes in behaviour and memory. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

*Information on: Ethylbenzene*

*Experimental/calculated data:*

*LD50 rat (oral): 3.500 mg/kg*

*Literature data.*

*Information on: Xylene*

*Experimental/calculated data:*

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

*LD50 rat (oral): 3.523 mg/kg (similar to OECD guideline 401)*  
-----

*Information on: Ethylbenzene  
Experimental/calculated data:  
LD50 rabbit (dermal): 15.354 mg/kg  
Literature data.*  
-----

#### Irritation

Assessment of irritating effects:

The liquid splashed in the eyes may cause irritation and reversible damage. Eye contact causes irritation. Skin contact causes irritation.

#### Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

#### Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

#### Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

### Aspiration hazard

No aspiration hazard expected.

---

## 12. Ecological Information

### Toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life with long lasting effects. Toxic to aquatic life. There are no test results available for this product. Do not allow to enter drains or waterways.

### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Biological degradability of hazardous substances mentioned in section 3:

*Information on: 1,2,4-Trimethylbenzene*

*Elimination information:*

*> 20 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: Ethylbenzene*

*Elimination information:*

*70 - 80 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge) Readily biodegradable (according to OECD criteria).*

*Information on: Mesitylene*

*Elimination information:*

*61 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, other)*

*Information on: n-Butyl acetate*

*Elimination information:*

*80 % BOD of the ThOD (5 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, municipal sewage treatment plant effluent)*

*Information on: Xylene*

*Elimination information:*

*87,8 % BOD of the ThOD (28 d) (OECD Guideline 301 F) (aerobic, activated sludge, domestic, non-adapted)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

*Information on: Solvent naphtha (petroleum), light arom.*

*Elimination information:*

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

*77 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic, non-adapted)*

*96 % CO<sub>2</sub> formation relative to the theoretical value (28 d) (ISO 14593) (aerobic, activated sludge, domestic, adapted)*

*Information on: Naphtha (petroleum),hydrotreated light, Kp > 140oC*

*Elimination information:*

*9 % BOD of the ThOD (28 d) (OECD 301D; EEC 92/69, C.4-E) (aerobic, domestic sewage, adapted)*

*The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*

### **Bioaccumulative potential**

Bioaccumulation potential:  
No data available.

### **Mobility in soil**

Assessment transport between environmental compartments:  
Adsorption in soil: No data available.

---

## **13. Disposal Considerations**

### **Waste treatment methods**

Observe national and local legal requirements.  
No disposal via sewage or waste water systems.

Contaminated packaging:  
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

## **14. Transport Information**

### **Land transport**

ADR

UN number	UN1263
UN proper shipping name:	PAINT
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Special precautions for user: Tunnel code: D/E

**RID**

UN number: UN1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: None known

**Inland waterway transport****ADN**

UN number: UN1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Special precautions for user: None known

**Transport in inland waterway vessel**

Not evaluated

**Sea transport****IMDG**

UN number: UN 1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3  
Packing group: III  
Environmental hazards: no  
Marine pollutant: NO  
Special precautions for user: None known

**Air transport****IATA/ICAO**

UN number: UN 1263  
UN proper shipping name: PAINT  
Transport hazard class(es): 3

Safety data sheet according to UN GHS 4th rev.  
Date / Revised: 30.10.2021  
Product: **N15-020 Clear 5L**

Version: 3.0

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

### Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

## 15. Regulatory Information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

## 16. Other Information

For multi-pack systems observe material safety data sheets of all components. Restricted to professional users.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Flam. Liq.	Flammable liquids
Skin Sens.	Skin sensitization
Asp. Tox.	Aspiration hazard
Acute Tox.	Acute toxicity
STOT RE	Specific target organ toxicity — repeated exposure
Repr.	Reproductive toxicity
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H303	May be harmful if swallowed.
H373	May cause damage to organs (Auditory organ) through prolonged or repeated exposure.



---

Safety data sheet according to UN GHS 4th rev.

Date / Revised: 30.10.2021

Version: 3.0

Product: **N15-020 Clear 5L**

(ID no. 50655494/SDS\_GEN\_00/EN)

Date of print 08.11.2021

H412	Harmful to aquatic life with long lasting effects.
H305	May be harmful if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H320	Causes eye irritation.
H333	May be harmful if inhaled.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

---

Vertical lines in the left hand margin indicate an amendment from the previous version.